

Wave Nano



Mechanical

Dimensions	Ø256.5 x 113.5 mm (Ø10.1 x 4.5")
Weight	Without mount: 932 g (2.1 lb) With mount: 1.2 kg (2.6 lb)
Enclosure materials	Aluminum alloy, UV stabilized plastic
Mount materials	Aluminum alloy, UV stabilized plastic
Pole mount diameter	25 to 63.5 mm (1 to 2.5") on pipe outer diameter
Wind loading	127 N at 200 km/h (28.6 lbf at 125 mph)
Weatherproofing	IPX6

Hardware

Processor	Dual ARM® Cortex®-A53 cores at 1GHz
Memory	DDR3L 512MB
Networking interface	(1) GbE RJ45 port
Max. power consumption	18W
Power method	48VDC passive PoE 4-pairs (1, 2+; 3, 6-) (4,5+; 7, 8-) or 2-pairs (4, 5+; 7, 8-) 24VDC passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-)
Power supply	48VDC, 0.65A gigabit PoE adapter (included) Can be powered by a UISP Router or UISP Switch
Button	Factory reset
LEDs	Power, Ethernet, GPS, link
Operating temperature	-40 to 60° C (-40 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	FCC, IC, CE

Software

OS	airOS®
Operating mode	PtMP station
Ubiquiti specific features	Integrated 60 GHz radio, discovery protocol, Wave technology
Services	UISP, ping watchdog, NTP client, SNMP
Tools	Antenna alignment, discovery utility, ping, trace route, speed test
Network	Bridge/Router mode
Software management	Bluetooth management for easy setup over UISP app WEB UI
Minimum software requirements	Any modern web browser/iOS or Android based smartphone

System

Total throughput	2 Gbps (1 Gbps duplex)
------------------	------------------------

Maximum range	5 km
Encryption	WPA2-PSK (AES)

RF

Operating frequency*	57 to 71 GHz <small>*Depends on regulatory region.</small>
GPS	Yes
Channel bandwidth	2160, 1080 MHz
Operating channels*	58320, 59400, 60480, 61560, 62640, 63720, 64800, 65880, 66960, 68040, 69120, 70200 MHz <small>*Depends on regulatory region.</small>
Modulation	16QAM, QPSK
Antenna gain	41 dBi
Azimuth and elevation beamwidth	3 dB: 1° 6 dB: 1.4°

Back-Up RF

WiFi standard	802.11ax (WiFi 6)										
Operating frequency*	<table border="1"> <tr> <td rowspan="2">US/CA</td> <td>U-NII-1</td> <td>5150 - 5250 MHz</td> </tr> <tr> <td>U-NII-3</td> <td>5725 - 5850 MHz</td> </tr> <tr> <td>Worldwide</td> <td colspan="2">5150 - 5875 MHz</td> </tr> </table>	US/CA	U-NII-1	5150 - 5250 MHz	U-NII-3	5725 - 5850 MHz	Worldwide	5150 - 5875 MHz		<small>*Depends on regulatory region.</small>	
US/CA	U-NII-1		5150 - 5250 MHz								
	U-NII-3	5725 - 5850 MHz									
Worldwide	5150 - 5875 MHz										
Channel bandwidth	20, 40, 80 MHz										
Modulation	BPSK (½), QPSK (½), QPSK (¾), 16QAM (½), 16QAM (¾), 64QAM (2/3), 64QAM (¾), 64QAM (5/6), 256QAM (¾), 256QAM (5/6), 1024QAM (¾), 1024QAM (5/6)										
Antenna gain	19 dBi										
Polarization	Dual-linear										
Cross-pol isolation	20 dB										
Beamwidth	Azimuth: 3 dB BW 14 to 17° Elevation: 3 dB BW 14 to 17°										
Azimuth and elevation beamwidth	3 dB: 14 to 17°										

LEDs

Power	Flashing white: bootup in progress White: not connected to UISP application Blue: connected to UISP application Flashing blue: locate in progress Blue/white: firmware upgrade in progress
Ethernet	Flashing blue: Ethernet traffic detected
GPS	Blue: receiving at least (4) GPS satellite signal
Links	White: 5GHz link Blue: 60GHz link

